# ECO-CLEAR Submersible Pond Pumps



Eco-Clear Submersible Pond Pumps feature a permanent magnet motor for high efficiency and continuous duty. The epoxy sealed motor is safer for fish because there's no oil to leak out. Check out all the extra features!





Permanent Magnet Motor



Multi-Step Fittings



Durable Ceramic Impeller



Adjustable Outlet



Protective Housing



2" Outlet for Higher Flows



Convenient Handle



Flow Control (EPS4900VF Model)





EasyPro

Eco-Clear Complete System

Eco-Clear Pumps are also available in a complete kit with Eco-Clear Filters. It's complete pond filtration made simple!

### EASYPRO.COM

### 800-448-3873

# ECO-CLEAR Submersible Pond Pumps

**Features** 

- Permanent magnet motor for high efficiency and continuous duty
- Epoxy sealed motor no oil to leak out! Safe for fish.
- Ceramic impeller provides high wear resistance and long life – designed for passing debris up to <sup>3</sup>/<sub>8</sub>" diameter
  - Adjustable direction outlet includes 1", 1<sup>1</sup>/<sub>4</sub>" or 1<sup>1</sup>/<sub>2</sub>" step barb fitting
  - Variable flow model EPS4900VF available with external flow control module
- Three year warranty

#### **Performance Data**

	Max	Gallons per hour (gph) flow at feet of head									Max
Model	Watts	0'	3'	6'	9'	12'	15'	18 <sup>,</sup>	21'	24'	Lift
EPS1300	55	1400	1125	710	430	150	-	-	-	-	14.5'
EPS2500	87	2480	1680	1140	815	449	185	-	-	-	16'
EPS3700	150	3680	2900	2310	1815	1390	875	180	-	-	19'
EPS4900	190	4850	4090	3215	2425	1800	1400	832	195	-	22'
EPS4900VF	190	4850	4090	3215	2425	1800	1400	832	195	-	22'

\*Performance data provided for reference only and may vary slightly.

**Distributed by:** 

Splits the water flow so you can operate two features from a single pump.

Three-Way

1 1/4", 1 1/2", 2" inlet step barb 1", 1 1/4", 1 1/2" outlet step barb ECM3V