



# Premium Pond Flex Specifications

EasyPro smooth ID and OD black flexible PVC pipe. Designed to glue into Sch. 40 fittings using recommended PVC cements and primers. Temperature range: -10 to 130°F. Made in USA from virgin materials.

<b>Nominal I.D. Size</b>	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	3"
<b>O.D. (Inches)</b>	.84	1.05	1.315	1.66	1.900	2.375	3.5
<b>Working PSI @ 72°F (in psi)</b>	100	100	100	80	65	60	60
<b>Recom. Min. Bend Radius</b>	2"	2"	2"	4"	5"	6"	7"
<b>Approx Wt. (lbs per foot)</b>	.15	.2	.28	.34	.45	.62	1.28

# Ultimate Pond Flex Specifications

Smooth ID and OD black flexible PVC pipe. Designed to glue into Sch. 40 fittings using recommended PVC cements and primers. Temperature range: -10 to 130°F. Made in USA from virgin materials.

<b>Nominal I.D. Size</b>	1 1/2"	2"	3"	4"	6"
<b>I.D.</b>	1.59"	2.04"	3.07"	4.01"	5.84"
<b>O.D.</b>	1.91"	2.38"	3.50"	4.50"	6.61"
<b>Working PSI @ 68°F (in psi)</b>	85	70	50	50	50
<b>Burst @ 68°F (in psi)</b>	255	210	150	150	150
<b>Burst @ 140°F (in psi)</b>	100	90	75	75	*
<b>Recom. Min. Bend Radius @ 70F</b>	5"	6"	8"	11"	16"
<b>Approx Wt. (lbs per foot)</b>	0.5	.7	1.27	1.93	4.42

\*Not Recommended at 140°