# **QUIET**LIKE YOU'VE NEVER HEARD BEFORE



Noise reduction technology

exclusive to EasyPro® Aeration



# Stratus™ Rocking Piston Compressors with Sound Shield™

EasyPro's best selling Stratus™ SRC Series "Gen 2" Rocking Piston Compressors with the addition of revolutionary Sound Shield technology are the quietest compressors of their class in the industry!

These compressors are specifically designed for the demanding job of 24 hour operation. The oil-less design makes them ideal for lake and pond aeration systems. 1/4, 1/2, 3/4 and 2 hp models available. Stratus™ SRC Series Compressors are assembled in the USA.



### **Features**

- · Sound Shield Noise Reduction Technology
- Universal dual voltage, 1725 RPM (50/60Hz) motor
- · Oil-less operation
- · Permanently lubricated bearings
- Includes Stratus<sup>™</sup> Smart-Start technology to start under load
- Superior quality, flexible cup material for increased reliability
- · Die-cast body components for overall strength
- All units include air inlet filter, rubber feet and 5' power cord











Don't !!	l	W. Inc	A		Motor	Max	cfm Air Flow @ Water Depth of:						Inlet/Outlet	Power	Ship	N.* I I ××
Part#	hp	Volts	Amps*	Hz	Туре	PSI	0'	10'	20'	30'	40'	50'	Size	Cord	Weight	Noise Level**
SRC25SS	1/4	115	1.7	60	4 Pole	30	2.3	2.2	2.0	1.9	1.8	1.7	1/4" fpt	5'	17 lbs.	49 dBa
SRC252SS	1/4	230	0.9	60	4 Pole	30	2.3	2.2	2.0	1.9	1.8	1.7	1/4" fpt	5'	21 lbs.	49 dBa
SRC50SS	1/2	115	3.6	60	4 Pole	30	4.5	4.3	4.2	4.0	3.8	3.6	1/4" fpt	5'	22 lbs.	55 dBa
SRC502SS	1/2	230	1.8	60	4 Pole	30	4.5	4.3	4.2	4.0	3.8	3.6	1/4" fpt	5'	27 lbs.	55 dBa
SRC34SS	3/4	115	7.4	60	4 Pole	145	5.5	5.4	5.2	5.0	4.8	4.6	1/4" fpt	5'	26 lbs.	58 dBa
SRC342SS	3/4	230	3.8	60	4 Pole	145	5.5	5.4	5.2	5.0	4.8	4.6	1/4" fpt	5'	26 lbs.	58 dBa
SRC2002SS	2	230	10.0	60	4 Pole	125	12	11.7	11.4	11.2	10.8	10.5	3/8" fpt	5'	62 lbs.	67 dBa


<sup>\*</sup>Amps measured at 10' operating depth \*\*dBa measured without cabinet @ 3psi - your results will likely be quieter.




### SRC25SS/252SS










## SRC50SS/502SS









# SRC34SS/342SS







### **SRC2002SS**

